



T600 Thermal Platform Ordering Information

T600

Size

- 1 6.75" X 6.75" (17.15 cm X 17.15 cm)
- 2 6.75" X 13.25" (17.15 cm X 33.66 cm)
- 3 6.75" X 20.00" (17.15 cm X 50.80 cm)
- 4 6.75" X 26.25" (17.15 cm X 50.80 cm)
- 5 11" X 11" (27.94 cm X 27.94 cm)
- 6 11" X 22" (27.94 cm X 55.88 cm)
- 7 10" X 15" (25.4 cm X 38.1 cm)
- 8 15" X 15" (38.1 cm X 38.1 cm)
- 9 18" X 22" (45.75 cm X 55.88 cm)

Voltage

- 1 115 VAC 50/60 Hz
- 2 230 VAC 50/60 Hz

Coolant

- 1 LN₂ 15-25 PSIG (+130° C to -99° C)
- 2 LCO₂ 300 PSIG (+130° C to -65° C)
- 3 LCO₂ 900 PSIG (+130° C to -65° C)

Controller

- A Model PM9 with serial 232 Modbus RTU
- B Model PM9 with serial 232 Modbus RTU & GPIB-488
- C Model PM9 with Ethernet/IP, Modbus TCP

Country

- A Continental Europe
- C Australia/New Zealand
- D United Kingdom/Ireland
- E Denmark
- F France/Belgium
- G India/South Africa
- H Israel
- I Italy
- J Japan
- K USA (North America)
- L Switzerland
- O Russia
- X China
- T Argentina

Example: T600-113AK T600 Thermal Platform System, 6.75" X 6.75", 115 VAC 50/60 Hz, LCO₂ 900 PSIG, PM9 Controller with serial 232, North America (USA) plug on power cord