



T650 Thermal Platform Ordering Information

T650

Size

- 1 6.75" X 6.75" (17.15 cm X 17.15 cm)
- 2 11" X 11" (27.94 cm X 27.94 cm)

Voltage

- 1 115 VAC 50/60 Hz (110 to 120 VAC)
- 2 230 VAC 50/60 Hz (208 to 240 VAC)

Coolant

- 1 LN₂ 15-25 PSIG (+130° C to -99° C)
- 2 LCO₂ 300 PSIG (+130° C to -65° C)
- 3 LCO₂ 900 PSIG (+130° C to -65° C)

PM6 Controller

- A Premium — Ramp & soak profiling, Modbus RTU EIA-232/485 serial and 2nd user device sensor
- B Special — Contact ESS for options such as Ethernet/IP or integrated limit/alarm controller ("product saver")

Country

- A Continental Europe (Austria, Germany, Netherlands, Spain, Sweden, etc.)
- C Australia/New Zealand
- D United Kingdom/Ireland
- E Denmark
- F France/Belgium
- G India/South Africa
- H Israel
- I Italy
- J Japan
- K USA (North America)
- L Switzerland
- O Russia
- X China
- T Argentina
- Z Stripped Leads (no plug on power cord)

Example: T650-113AK

T650 Thermal Platform System, 6.75" X 6.75", 115 VAC 50/60 Hz, LCO₂ 900 PSIG, Premium PM6 Temperature Controller and USA (North America) plug and power cord